



DECLARATION OF PERFORMANCE

No.ECO.003CPR2013-07-01

1. Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with low water absorption $E_b \leq 0,5 \%$
2. Intended use(s)
For internal and external, floorings and wall finishes
3. Name or registered trade mark, and contact address of the manufacturer
ECOCERAMIC, S.L.U.
Avda. Mediterraneo, 86
12200 Onda (Castellón) SPAIN
4. System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
5. Name and identification number of notified laboratory, if relevant – **not applicable**
Task(s) carried out
AVCP system
Document issued and date of issue
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1_{FL}/A1	EN 14411:2012
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Eduardo Caballer (Manager)

Name and function

Onda, 01-01-2021

Place and date of issue

Signature